

borg &  
overström



Distinctive  
by design.

u2

# borg& overström

## High-performance hydration

Practical, reliable and visually striking, this innovative tap brings a high capacity refreshment solution to any commercial or Horeca environment.

---

### Reasons to choose

- High capacity output
- Low energy consumption
- Compact under-counter unit
- Robust, solid build quality
- Simple to operate and maintain
- Drip tray and ventilation kit included

[borgandoverstrom.com](http://borgandoverstrom.com)



---

Distinctive  
by design.

# u2

## Water system



Direct Chill



Undercounter

## Water options



Chilled



Ambient



Sparkling

## Configuration



Distinctive  
by design.

## Catering for capacity

The U2 boasts a compact yet high capacity under-counter appliance. It delivers a speedy throughput of 40 litres per hour at a consistent chilled temperature, making it the perfect solution for busy environments including Horeca applications.

## Borg & Overström Totality™



Driven by a relentless pursuit of excellence, Borg & Overström Totality™ is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



**Ultra-violet sterilising system**  
For added hygiene confidence, appliances can be fitted with Viovand™ – an ultra-violet sterilisation process that reduces water-born bacteria.



**Laboratory certified 99.999% bacteria-free**  
Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitising procedure. The reassurance of hygienically safe appliances is provided by the unique bacteria-eliminating process, Sterizen™.



**World-class filtration**  
For the ultimate drinking experience, Borg & Overström appliances can be pre-fitted with a 3M filter to reduce sediment, chlorine, odours and scale.

Distinctive  
by design.

U2 models	Undercounter - S2 W330xD370xH362mm	Water system	Dispense height	Max power consumption	Stainless Steel	Tap style
Power requirements Hertz 50/Volts 230	Chilled & Ambient	Dry Chill™	286mm	300W	601511	Twin Head W155xD240xH470mm
Chilled temperature Min 1°C/Max 12°C	Chilled & Sparkling	Dry Chill™	286mm	323W	601512	Twin Head W155xD240xH470mm
Throughput litres per hour S2 High-capacity chilled 40	Chilled, Ambient & Sparkling	Dry Chill™	286mm	323W	601513	Triple Head W215xD240xH470mm

Distinctive  
by design.

## Additions for U2



### Printed paper cups

Environmentally-friendly disposable cups designed to fit Borg & Overström cup dispensers perfectly.



### 750ml glass bottles

Suitable for dishwashers and bottlewashers. Perfect fit for the U2 tap. Stylish swing-top lid.



### Deep Sparkle™ CO<sup>2</sup> refills

Can be disposed via standard steel recycling or general waste. Requires CO<sup>2</sup> regulator with gauge.



### Sanitisation kit

Six monthly sanitising cycles ensure appliances function at the optimum hygiene levels.



### Waste kit overflow sensor

Featuring an audible high-water level alarm to prevent the waste tank from overflowing.



### Freestanding drip tray

Alternative non-plumbed drip tray for where integrated drip trays cannot be used.



### Install kit with 3M filter

Install appliances simply and effectively in a wide range of applications. Complete with a 3M filter.



### Ultra-violet filter kit

Complete Viovandt™ filter kit to assist in water purification and removal of unwanted micro-organisms.

Distinctive  
by design.

Book a visit to the Borg & Overström Academy  
for a personal demonstration of the new U2

Talk to an adviser  
**+44 (0) 1362 695 006**  
[sales@borgandoverstrom.com](mailto:sales@borgandoverstrom.com)